



PREMIUM QUALITY FIBERGLASS CLOTH

An AMATEX woven thermoglass fabric of a heavier weight in a plain weave. Applications include pads, curtains, blanket materials, insulation fabrics substrate for rubber coating. Resistant to most chemicals, offers good thermal protection to temperatures up to 1000 degrees F.

About AMATEX Corporation

Amatex manufactures industrial heat resistant textiles featuring Thermoglass™ fiberglass products, silica fabrics, and proprietary treated and coated products. These items include broad woven roll goods and narrow products in the form of woven and knitted tapes, sleeving, rope, and gasketing. With fiberglass and silica as the base textile, Amatex offers top and immersion coatings of Silicone, Teflon, Vermiculite, Neoprene, and Acrylic. Heat treating, dyeing, and coloration of the coatings are also available.

Amatex fabrics are commonly used in the following applications:

- Welding Cloth
- Foundry Cloth
- Insulation Cloth
- Heat Shield
- Gasketing
- Marine Insulation
- Industrial Insulation
- Pad Cloth
- Fire Barriers
- Fire Curtains
- Industrial Belting
- Filtration
- Expansion Joints
- Protective Clothing

Over 100 Years

Proud American Manufacturers of Industrial Textiles

Premium Quality Fiberglass Cloth Specifications

G32P44-31	
Base Fabric	Fiberglass
Color/Appearance	White
Available Widths, standard	40", 60" (1.0, 1.5)
Roll Length, yards	50 (45.7m)
Weave Style	Plain
Fabric Weight, oz./sq yd, average	32 (1080 gm/sq.m)
Fabric Thickness, inches	0.055 (1.40mm)
Warp Strength, lbs/in.	300.0 (136 Kg/2.54cm)
Fill Strength, lbs/in.	280.0 (127 Kg/2.54cm)
Abrasion Resistance	Good
Temperature Tolerance	To 1000 deg. F (540 deg. C) Higher for very brief periods.
Chemical Resistance	Excellent except Hydrofluoric and hot Phosphoric acid and wet Hydrogen Chloride
Solvent Resistance	Excellent
Sunlight & Age Resistance	Excellent
Electrical Properties	High dielectric strength, low constants
Available Finishes	
Finish Number	31 Heat Treat, 32 Weave Set, 33 Water Repellant, 35 Flame Retardant, 37 Color Dyed, 39 Firm Hand, and other combinations; See Fabric Finish Options data sheet



1032 Stanbridge Street,
 Box 228, Norristown, PA 19404-0228 U.S.A.
 Tel: 610-277-6100 • 800-441-9680 • Fax: 610-277-6106
 Email: sales@amatex.com • www.amatex.com