



06PT23- -30

NOR*FAB SERIES 400
6 oz. CLOTH

style 06PT23- -30

A NORFAB woven light weight fabric of Aramid fiber blend over a fiberglass core yarn, wear resist coated. Applications include use as a substrate fabric for silicone coating and for rubberized coatings. Resistant to heat sources, offers good thermal protection and as a liner for safety garments.

SPECIFICATIONS

BASE FABRIC	Aramid/Fiberglass	
COLOR / APPEARANCE	Yellow	
AVAILABLE WIDTHS, standard	40", 60"	(1.0, 1.5m)
ROLL LENGTH, yards	50	(45.7m)
WEAVE STYLE	Plain	
CONSTRUCTION, ends x picks/sq.in	21 X 19	(8.3 x 7.5/cm)
FABRIC WEIGHT, oz./sq yd, average	6.0	(204 gm/sq.m)
FABRIC THICKNESS, inches	0.028	(0.71mm)
WARP STRENGTH, lbs/in.	130.0	(59 Kg/2.54 cm)
FILL STRENGTH, lbs/in.	60.0	(27 Kg/2.54 cm)
ABRASION RESISTANCE	Good	
THERMAL CONDUCTIVITY, "K" factor (Btu x in/hr x sqft x deg. F)	n/a (ASTM D2214-70)	
TOTAL CONDUCTANCE, "C" factor (Btu/hr x sqft x deg. F)	n/a (ASTM D2214-70)	
TOTAL RESISTANCE, "R" factor (Hr x sqft x deg. F/Btu)	n/a (ASTM D2214-70)	
COATING / LAMINATION	30, Wear Resist	
SOLVENT & CHEMICAL RESISTANCE	Good	
SUNLIGHT & AGE RESISTANCE	Base fabric is UV sensitive	
ELECTRICAL PROPERTIES	n/a	

AVAILABLE FINISHES

FINISH NUMBER 30, Wear Resist
See FABRIC FINISH OPTIONS data sheet.

JE/J

AMATEX Corporation is the exclusive sales agent for
NOR*FAB Corporation "HEAT RESISTANT TEXTILES"

BOX 228, 1032 STANBRIDGE STREET, NORRISTOWN, PA 19404 USA
 PHONE 1-610-277-6100 • TOLL FREE 1-800-441-9680 • FAX 1-610-277-6106

All data intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by AMATEX or NOR*FAB Corp.