



**NOR\*FAB**

# 30PT307DC- -39

**NOR\*FAB SERIES 800**  
**30 oz. DOUBLE CLOTH**

## style 30PT307DC- -39 (w/Reconditioned Fiber)

A NORFAB woven heavy weight double fabric of an Aramid fiber blend over a fiberglass core yarn. Applications include very heavy safety clothing, jackets, curtains, and other industrial applications. Resistant to high heat sources, offers excellent thermal protection for heavier required safety garments.

### SPECIFICATIONS

BASE FABRIC	PBi-Aramid/Fiberglass	
COLOR / APPEARANCE	Ochre	
AVAILABLE WIDTHS, standard	40"	(1.0m)
ROLL LENGTH, yards	50	(45.7m)
WEAVE STYLE	Plain	
CONSTRUCTION, ends x picks/sq.in	30 x 13	(11.8 x 5.1/cm)
FABRIC WEIGHT, oz./sq yd, average	30	(1019 gm/sq.m)
FABRIC THICKNESS, inches	0.114	(2.89 mm)
WARP STRENGTH, lbs/in.	550.0	(250 Kg/2.54 cm)
FILL STRENGTH, lbs/in.	370.0	(168 Kg/2.54 cm)
ABRASION RESISTANCE	Excellent	
THERMAL CONDUCTIVITY, "K" factor (Btux in/hr x sqft x deg. F)	n/a (ASTM C-177)	
TOTAL CONDUCTANCE, "C" factor (Btu/hr x sqft x deg. F)	n/a (ASTM C-177)	
TOTAL RESISTANCE, "R" factor (Hr x sqft x deg. F/Btu)	n/a (ASTM C-177)	
COATING CERTIFICATIONS	n/a	
SOLVENT RESISTANCE	n/a	
SUNLIGHT & AGE RESISTANCE	Base fabric is UV sensitive	
ELECTRICAL PROPERTIES	n/a	

### AVAILABLE FINISHES

FINISH NUMBER 39, Firm Hand  
See FABRIC FINISH OPTIONS data sheet.

JE/J

Note: All data +/-10%

AMATEX Corporation is the exclusive sales agent for

**NOR\*FAB Corporation** "HEAT RESISTANT TEXTILES"

BOX 228, 1032 STANBRIDGE STREET, NORRISTOWN, PA 19404 USA  
PHONE 1-610-277-6100 • TOLL FREE 1-800-441-9680 • FAX 1-610-277-6106

All data intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by AMATEX or NOR\*FAB Corp.