



NOR*FAB

07TT217- -30

**NOR*FAB 900 SERIES 7 oz. CLOTH
A PATENT PROTECTED FABRIC**

style 7TT217- -30

A NORFAB woven light weight fabric of an Aramid fiber blend over a "PAN" core yarn.
Applications include light weight safety clothing, gloves, mitts, jackets, and other industrial applications.
Resistant to moderate heat sources, offers very good thermal protection for safety garments.

SPECIFICATIONS

BASE FABRIC	Aramid cover with "PAN" insert	
COLOR / APPEARANCE	Light pea green	
AVAILABLE WIDTHS, standard	41"	(1.04m)
ROLL LENGTH, yards	50	(45.7m)
WEAVE STYLE	2/2 Twill	
CONSTRUCTION, ends x picks/sq.in	52 X 51	(20.5 x 20.1/cm)
FABRIC WEIGHT, oz./sq yd, average	6.71	(228 gm/sq.m)
FABRIC THICKNESS, inches	0.020	(0.46mm)
WARP STRENGTH, lbs/in.	130.0	(59 Kg/2.54 cm)
FILL STRENGTH, lbs/in.	115.0	(52 Kg/2.54 cm)
ABRASION RESISTANCE	Very Good	
THERMAL CONDUCTIVITY, "K" factor (Btu x in/hr x sqft x deg. F)	n/a	(ASTM C-177)
TOTAL CONDUCTANCE, "C" factor (Btu/hr x sqft x deg. F)	n/a	(ASTM C-177)
TOTAL RESISTANCE, "R" factor (Hr x sqft x deg. F/Btu)	n/a	(ASTM C-177)
COATING CERTIFICATION	n/a	
SOLVENT RESISTANCE	n/a	
SUNLIGHT & AGE RESISTANCE	Base fabric is partially UV sensitive	
ELECTRICAL PROPERTIES	n/a	

AVAILABLE FINISHES

FINISH NUMBER 30, Wear resist
See FABRIC FINISH OPTIONS data sheet.

JE/1

AMATEX Corporation is the exclusive sales agent for

NOR*FAB Corporation "HEAT RESISTANT TEXTILES"

BOX 228, 1032 STANBRIDGE STREET, NORRISTOWN, PA 19404 USA
PHONE 1-610-277-6100 • TOLL FREE 1-800-441-9680 • FAX 1-610-277-6106

All data intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by AMATEX or NOR*FAB Corp.