



30PT232- -45

NOR*FAB SERIES 1200
67 oz. TACKY CLOTH
WITH BRASS INSERT

style 30PT232- -45

A NORFAB woven heavy weight fabric of carded glass blend with brass insert and tacky style coating. Applications include multiple layer fabrication of gaskets and similar preformed items. Resistant to high heat sources, offers excellent thermal protection with outstanding gasketing qualities.

SPECIFICATIONS

BASE FABRIC	Aramid/Fiberglass/Brass Wire	
COLOR / APPEARANCE	White Coated	
AVAILABLE WIDTHS, standard	40"	(1.0m)
ROLL LENGTH, yards	50	(45.7m)
WEAVE STYLE	Plain	
CONSTRUCTION, ends x picks/sq.in	10 x 8.5	(3.9 x 3.3/cm)
FABRIC WEIGHT, oz./sq yd, average, coated	67	(2276 gm/sq.m)
FABRIC THICKNESS, inches	0.112	(2.84mm)
WARP STRENGTH, lbs/in.	255.0	(116 Kg/2.54 cm)
FILL STRENGTH, lbs/in.	260.0	(118 Kg/2.54 cm)
ABRASION RESISTANCE	Excellent	
THERMAL CONDUCTIVITY, "K" factor (Btux in/hr x sqft x deg. F)	n/a (ASTM C-177)	
TOTAL CONDUCTANCE, "C" factor (Btu/hr x sqft x deg. F)	n/a (ASTM C-177)	
TOTAL RESISTANCE, "R" factor (Hr x sqft x deg. F/Btu)	n/a (ASTM C-177)	
COATING CERTIFICATIONS	n/a	
SOLVENT RESISTANCE	n/a	
SUNLIGHT & AGE RESISTANCE	Base fabric is UV sensitive before coating	
ELECTRICAL PROPERTIES	n/a	

AVAILABLE FINISHES

FINISH NUMBER 45, Tacky Coating
See FABRIC FINISH OPTIONS data sheet.

JE/J

AMATEX Corporation is the exclusive sales agent for
NOR*FAB Corporation "HEAT RESISTANT TEXTILES"
BOX 228, 1032 STANBRIDGE STREET, NORRISTOWN, PA 19404 USA
PHONE 1-610-277-6100 • TOLL FREE 1-800-441-9680 • FAX 1-610-277-6106
All data intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by AMATEX or NOR*FAB Corp.