



08TT298

100% TWARON 8 oz. SAFETY CLOTH FOR REINFORCEMENT FABRIC

-T-

style 08TT298

A NOR-FAB 100% Twaron fiber light weight fabric woven in a 3/1 twill pattern.
Applications include safety clothing reinforcements, aprons, cuffs, sleeves, capes, pockets, etc.
Resistant to some chemicals and solvents. Fabric is partially UV sensitive.

SPECIFICATIONS

BASE FABRIC	100% Twaron Fiber
COLOR / APPEARANCE	Yellow
AVAILABLE WIDTHS, standard	60" (1.5m)
ROLL LENGTH, yards	50 (45.7m)
WEAVE STYLE	3/1 Left Hand Twill, woven face down
CONSTRUCTION, ends x picks/sq.in.	53 X 39 (20.8 x 15.4/cm)
FABRIC WEIGHT, oz./sq yd, average	8.0 (271 gm/sq. m)
FABRIC THICKNESS, inches	0.026 (0.56mm)
WARP STRENGTH, lbs/in.	400 (182 Kg/2.54 cm)
FILL STRENGTH, lbs/in.	260 (118 Kg/2.54 cm)
ABRASION RESISTANCE	Very Good
THERMAL CONDUCTIVITY, "K" factor (Btu x in/hr x sqft x deg. F)	n/a (Results similar to 08TT132) (ASTM C-177)
TOTAL CONDUCTANCE, "C" factor (Btu/hr x sqft x deg. F)	n/a (Results similar to 08TT132) (ASTM C-177)
TOTAL RESISTANCE, "R" factor (Hr x sqft x deg. F/Btu)	n/a (Results similar to 08TT132) (ASTM C-177)
CHEMICAL RESISTANCE	n/a
SOLVENT RESISTANCE	n/a
SUNLIGHT & AGE RESISTANCE	Para-Aramid fibers UV sensitive
ELECTRICAL PROPERTIES	n/a

AVAILABLE FINISHES

FINISH NUMBER 30 Wear Resist, 39 Firm Hand
See FABRIC FINISH OPTIONS data sheet.

JHL

All data ±10%

AMATEX Corporation is the exclusive sales agent for

NOR-FAB Corporation "HEAT RESISTANT TEXTILES"

BOX 228, 1032 STANBRIDGE STREET, NORRISTOWN, PA 19404 USA
PHONE 1-610-277-6100 • TOLL FREE 1-800-441-9680 • FAX 1-610-277-6106

All data intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by AMATEX or NOR-FAB Corp.