

NOR•FAB BRAIDED SLEEVING

Nor•Fab Series 400 braided sleeving is manufactured in one style and two wall thicknesses. It is made using para-aramid fibers spun over a strong fiberglass core yarn.

These sleeveings, or tubular form of textiles, are widely used over electrical leads, cables and other conductors to provide abrasion resistance as well as fire protection. There are many other uses to which these products are applied.

GENERAL SPECIFICATIONS

SERIES 400 Braided Sleeving: •1/16" or 1/8" Wall Thickness. 100% para-aramid over glass core yarn.

STANDARD PRODUCTS

SERIES 400 Braided Sleeving	Style No.	Size I.D.	**Feet/Lb.	Approx. Ft./Lb.	
				15# Spool	25# Spool
1/16" Wall Thickness	400-0125-2	1/8"	140.0	2,100	3,500
"	400-0250-2	1/4"	86.0	1,290	2,150
"	400-0375-2	3/8"	42.0	630	1,050
"	400-0500-2	1/2"	40.0	600	1,000
"	400-0625-2	5/8"	31.0	465	775
"	400-0750-2	3/4"	28.0	420	700
"	400-0875-2	7/8"	24.6	369	615
"	400-1000-2	1"	23.3	350	583
"	400-1250-2	1 1/4"	21.0	315	525
"	400-1500-2	1 1/2"	15.5	232	387
"	400-1750-2	1 3/4"	12.0	180	300
"	400-2000-2	2"	11.5	172	287
"	400-2250-2	2 1/4"	10.5	157	262
1/8" Wall Thickness	400-1625-3	1 5/8"	10.1	152	253
"	400-2500-3	2 1/2"	7.0	105	175
"	400-3000-3	3"	6.1	92	153
"	400-4000-3	4"	3.6	54	90
"	400-4500-3	4 1/2"	3.4	51	85
"	400-5000-3	5"	2.8	42	70

** Measured over mandrel • 25# Spools standard • 15# Spools adds 10% to cost • All data ±10%
Other sizes may be available. Minimums may apply. Inquire with our Sales office at 1-800-441-9680.

AMATEX Corporation is the exclusive sales agent for

NOR*FAB Corporation "HEAT RESISTANT TEXTILES"

BOX 228, 1032 STANBRIDGE STREET, NORRISTOWN, PA 19404 USA
PHONE 1-610-277-6100 • TOLL FREE 1-800-441-9680 • FAX 1-610-277-6106

All data intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by AMATEX or NOR*FAB Corp.



NOR*FAB