

# G35PAA- -00

35 oz. INDUSTRIAL QUALITY  
FIBERGLASS FABRIC

## style G35PAA- -00

An AMATEX woven roving thermoglass fabric of a heavier weight in a plain weave.  
Applications include all general industrial uses such as blankets and protective curtains.  
Resistant to most chemicals, offers thermal protection for temperatures up to 1000 degrees F.

## SPECIFICATIONS

BASE FABRIC	Fiberglass	
COLOR / APPEARANCE	White	
AVAILABLE WIDTHS, standard	40", 60"	(1.0m, 1.5m)
ROLL LENGTH, yards	50	(45.7m)
WEAVE STYLE	Plain	
CONSTRUCTION, ends x picks/sq.in.	10 X 9	(3.9 x 3.5/cm)
FABRIC WEIGHT, oz./sq yd, average	35	(1189 gm/sq. m)
FABRIC THICKNESS, inches	0.045	(1.14 mm)
WARP STRENGTH, lbs/in.	300.0	(136 Kg/2.54cm)
FILL STRENGTH, lbs/in.	250.0	(114 Kg/2.54cm)
ABRASION RESISTANCE	Good	
TEMPERATURE TOLERANCE	To 1000 deg. F, base fabric (540 deg. C) Higher for very brief periods	
BASE FABRIC CERTIFICATIONS	n/a	
COATING CERTIFICATIONS	n/a	
CHEMICAL RESISTANCE	Excellent except Hydrofluoric and hot Phosphoric acid and wet Hydrogen Chloride.	
SOLVENT RESISTANCE	Excellent	
SUNLIGHT & AGE RESISTANCE	Excellent	
ELECTRICAL PROPERTIES	High dielectric strength, low constants	

## AVAILABLE FINISHES

FINISH NUMBER

See FABRIC FINISH OPTIONS data sheet.

JEA

# AMATEX Corporation

"HEAT RESISTANT TEXTILES"

BOX 228, 1032 STANBRIDGE STREET, NORRISTOWN, PA 19404 USA  
PHONE 1-610-277-6100 • TOLL FREE 1-800-441-9680 • FAX 1-610-277-6106

Data shown herein is intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by AMATEX Corp.

