

TACKY CLOTH

30 OZ. TACKY FIBERGLASS GASKET CLOTH

style G30PAB-40-45

An AMATEX woven roving thermoglass fabric, 30 oz. weight, plain weave with a special tacky coating. Applications include the manufacture of gasket products and tadpole tapes.

Resistant to most chemicals, offers thermal protection for temperatures up to 1000 degrees F. Tacky cloth should be stored at the recommended 68 deg. F. This product must be used prior to the expiration date found on the original packaging label. Retain this label and the roll number label for your records.

SPECIFICATIONS

BASE FABRIC	Fiberglass	
COLOR / APPEARANCE	White	
AVAILABLE WIDTHS, standard	40"	(1.0m)
ROLL LENGTH, yards	50	(45.7m)
WEAVE STYLE	Plain	
CONSTRUCTION, ends x picks/sq.in.	10 X 8	(3.9 x 3.1/cm)
FABRIC WEIGHT, oz./sq yd, average	61	(2072 gm/sq. m)
FABRIC THICKNESS, inches	0.082	(2.1mm)
WARP STRENGTH, lbs/in.	450.0	(205 Kg/2.54cm)
FILL STRENGTH, lbs/in.	350.0	(159 Kg/2.54cm)
ABRASION RESISTANCE	Very Good	
TEMPERATURE TOLERANCE	To 1000 deg. F, base fabric (540 deg. C) Higher for very brief periods	
BASE FABRIC CERTIFICATIONS	n/a	
COATING CERTIFICATIONS	n/a	
CHEMICAL RESISTANCE	n/a	
SOLVENT RESISTANCE	Excellent	
SUNLIGHT & AGE RESISTANCE	Excellent	
ELECTRICAL PROPERTIES	High dielectric strength, low constants	

AVAILABLE FINISHES

FINISH NUMBER 45, Tacky Coating

NOTE: Store Tacky Cloth at the recommended 68 deg. F. Use this product prior to the expiration date on the original packaging label. Retain this label and the roll number label for your records.

JE/K

AMATEX Corporation

"HEAT RESISTANT TEXTILES"

BOX 228, 1032 STANBRIDGE STREET, NORRISTOWN, PA 19404 USA

PHONE 1-610-277-6100 • TOLL FREE 1-800-441-9680 • FAX 1-610-277-6106

Data shown herein is intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by AMATEX Corp.

